ABA-6 2/1 banquet Trolley 6 GN capacity ABA-12 2/1 banquet Trolley 12 GN capacity ABA-10 2/1 banquet Trolley 10 GN capacity ABA-15 1/1 banquet Trolley 15 GN capacity



Atalay



- The capacity of the product should not be below the requirement.
- In accordance with the type of product to be served must be heated, cooled or neutral.
- The wheels of the product should be considered to be in the desired slickness.
- Otherwise, a large number of people may cause job loss by dealing with the transportation business of the trolley.
- To be in compliance with international standards will provide convenience when buying trays and tubs to be placed in the dimensions will provide an advantage to be in compliance with international standards.
- Ensure that cabin temperature is controllable and injectable.
- Not every food is suitable to wait at the same temperature.
- Heated banquette trolleys can be preferred with convection models to prevent moisture loss of food.

MODEL	ABA - 6 2/1	ABA - 10 2/1	ABA - 12 2/1	ABA - 15 1/1
Capacity	6	10	12	15
Dimensions	840 x 920 x 1090	740 x 950 x 1830	840 x 920 x 1780	590 x 870 x 1550
kW	1,65	1,70	2,35	2,05
Power	230 V	230 V	230 V	230 V
Wheigt	106 kg	136 kg	153 kg	142 kg



Banquette trolley was produced to facilitate the service of many people in organizations; It is a wheeled cart where plates, trays or refreshments are prepared and stored until the service, where they can be transported in bulk.

Heated banquette trolley with door convection system warm banquette trolley offers dry or moist air heating facilities to get the best result from your food.



- Made of stainless steel.

- -0-90° C digital thermostat is controlled. 2 wheels with brakes and 2 wheels without brakes.
- Shelf ranges can be adjusted.
- Body and door are double walled polyurethane insulation.
- Corner tire is used against bumps.
- It has humidification feature thanks to the heated pool at the base.



www.atalay.com.tr

